ERON


ロケーティングピンB型 RoHS対応


LOCATING PINS (TYPE B) No.E-9601



| 材 質 BS.970 Gr.080M15 | 熱処理 焼入HRC60 | 表面処理 | 黒染め

- ●外径A及びBはユーザー様にて許容差に合せて加工してだくさい。(セルフカット品)
- ●外径A及びB研削仕上(仕上品)





## ■仕様・価格表(セルフカット品)

\* 標準在庫品

オーダーNo.	No.	A <sup>+0.30</sup> <sub>+0.23</sub>	B <sup>+0.30</sup> <sub>+0.23</sub>	С	D	質量g	価格
* 914800	LP201B	8	6	16	2	6	2,650
* 914801	LP202B	10	6	16	3	7	2,650
* 914802	LP203B	12	8	18	3	11	2,690
* 914803	LP204B	14	8	18	4	11	2,850
* 914804	LP205B	15	10	20	4	18	2,970
* 914805	LP206B	16	10	20	4	21	3,200
* 914806	LP207B	18	10	20	5	21	3,220
* 914807	LP208B	20	12	24	5	28	3,300
* 914808	LP209B	22	12	24	6	34	3,560
* 914809	LP210B	24	12	24	6	34	3,920
* 914810	LP211B	25	12	24	6	40	3,940

## ■仕様·価格表(仕上品)

\* 標準在庫品

オーダーNo.	No.	Ag6	Aの許容差	Bp6	Bの許容差	С	D	質量g	価格
* 914811	LP251	8	-0.005 -0.014	6	+0.020 +0.012	16	2	6	5,800
* 914812	LP252	10	-0.005 -0.014	6	+0.020 +0.012	16	3	7	5,800
* 914813	LP253	12	-0.006 -0.017	8	+0.024 +0.015	18	3	11	6,400
* 914814	LP254	14	-0.006 -0.017	8	+0.024 +0.015	18	4	11	6,400
* 914815	LP255	15	-0.006 -0.017	10	+0.024 +0.015	20	4	18	6,700
* 914816	LP256	16	-0.006 -0.017	10	+0.024 +0.015	20	4	21	6,800
* 914817	LP257	18	-0.006 -0.017	10	+0.024 +0.015	20	5	21	6,800
* 914818	LP258	20	-0.007 -0.020	12	+0.029 +0.018	24	5	28	6,800
* 914819	LP259	22	-0.007 -0.020	12	+0.029 +0.018	24	6	34	7,150
* 914821	LP261	25	-0.007 -0.020	12	+0.029 +0.018	24	6	40	7,850

## ■使用例

