ロケーティングセンター ROHS対応

LOCATING CENTERS No.E-1232






材質 SCM420

熱処理 焼入 HRC60





■仕様·価格表

* 在庫限りで廃番

| オーダーNo. | No. | A+0.002 +0.010 | B ^{m5} | С | D | Е | F | 質量kg | 価格 |
|-----------------|------------|-------------------|-----------------|----|----|------|------|------|-------|
| * 124962 | BT412-107A | 12 | 20 | 48 | 28 | 0.01 | 0.01 | 0.08 | 1,480 |
| * 124963 | BT412-107B | 12 | 30 | 48 | 28 | 0.01 | 0.01 | 0.14 | 1,500 |
| * 124964 | BT412-107C | 12 | 40 | 48 | 28 | 0.01 | 0.01 | 0.23 | 2,000 |
| * 124965 | BT412-107D | 12 | 50 | 48 | 28 | 0.01 | 0.01 | 0.33 | 2,250 |
| * 124966 | BT516-107A | 16 | 20 | 48 | 28 | 0.01 | 0.01 | 0.10 | 1,500 |
| * 124967 | BT516-107B | 16 | 30 | 48 | 28 | 0.01 | 0.01 | 0.16 | 1,740 |
| * 124968 | BT516-107C | 16 | 40 | 48 | 28 | 0.01 | 0.01 | 0.25 | 1,750 |
| * 124969 | BT516-107D | 16 | 50 | 48 | 28 | 0.01 | 0.01 | 0.36 | 2,250 |

■使用例

