

ローテティングピン(インチ仕上)

LOCATING PINS No.E-9762

RoHS対応

ERON®



PIR

PID




材質 SCM435

熱処理 焼入HRC30±3

表面処理 黒染め


- インチ仕様の位置決めピンです。(A寸法のみ)
- 打ち込み作業の効率を上げるため、導入部が2段階に分けています。(研削仕上)
- 硬度を弱めに設定してあります。

▽▽ (▽▽▽)



PID

■ 使用例



■ サイズ表

No.	Ag ⁶	Aの許容差	Bp ⁶	Bの許容差	C	D	E	F	G	H
PI(R,D)0108	3.175(1/ 8")	-0.004 -0.012	6	+0.020 +0.012	13	6	2	3	1.2	50°
PI(R,D)0316	4.763(3/16")	-0.004 -0.012	6	+0.020 +0.012	16	6	2	3	1.5	50°
PI(R,D)0104	6.350(1/ 4")	-0.005 -0.014	8	+0.024 +0.015	25	10	3	3	2.2	60°
PI(R,D)0516	7.938(5/16")	-0.005 -0.014	8	+0.024 +0.015	25	10	3	3	2.2	60°
PI(R,D)0308	9.525(3/ 8")	-0.005 -0.014	12	+0.029 +0.018	30	10	3	4	3	60°
PI(R,D)0716	11.113(7/16")	-0.006 -0.017	12	+0.029 +0.018	34	12	4	4	3.5	60°
PI(R,D)0102	12.700(1/ 2")	-0.006 -0.017	14	+0.029 +0.018	36	12	4	4	4	60°
PI(R,D)0508	15.875(5/ 8")	-0.006 -0.017	16	+0.029 +0.018	42	12	4	5	5	60°
PI(R,D)0304	19.050(3/ 4")	-0.007 -0.020	20	+0.035 +0.022	47	15	5	5	6	60°
PI(R,D)0708	22.225(7/ 8")	-0.007 -0.020	25	+0.035 +0.022	49	15	5	6	8	60°
PI(R,D)1000	25.400(1")	-0.007 -0.020	28	+0.035 +0.022	49	15	5	6	9	60°

■ 仕様・価格表

* 在庫限りで廃番

PIR(丸ピン)					PID(ダイヤピン)				
オーダーNo.	No.	質量g	単品価格		オーダーNo.	No.	質量g	単品価格	
			1~9個	10個以上				1~9個	10個以上
* 955483	PIR0108	1	2,590	2,330	* 955494	PID0108	1	3,330	3,000
* 955484	PIR0316	2	2,590	2,330	* 955495	PID0316	2	3,330	3,000
* 955485	PIR0104	5	2,590	2,330	* 955496	PID0104	5	3,330	3,000
* 955486	PIR0516	9	2,590	2,330	* 955497	PID0516	9	3,330	3,000
* 955487	PIR0308	25	2,970	2,680	* 955498	PID0308	25	3,800	3,420
* 955488	PIR0716	28	3,030	2,730	* 955499	PID0716	28	3,910	3,520
* 955489	PIR0102	39	3,290	2,960	* 955500	PID0102	39	4,460	4,010
* 955490	PIR0508	62	3,470	3,120	* 955501	PID0508	62	4,510	4,060
* 955491	PIR0304	112	3,630	3,270	* 955502	PID0304	112	4,840	4,360
* 955492	PIR0708	180	3,880	3,500	* 955503	PID0708	180	5,050	4,560
* 955493	PIR1000	220	4,050	3,640	* 955504	PID1000	220	5,500	4,950