

クサビクランプ2 ベース付


RoHS対応

ERON®


WEDGE CLAMPS No.E-9460




- 材質 SCM440
 熱処理 本体：焼入 HRC30 ± 3 可動体：焼入 HRC50 ± 3
 表面処理 黒染め





可動体トウ




可動体グリップ



可動体V型



可動体フラット



■ 参照ページ

ソケットスク류ー



P.896 ▶

■ サイズ表

* 標準在庫品

オーダーNo	No.	可動体形状	A	B	C	D	E	F	G	H	I	J	K	L	M
*125680	DKC08-FJ	フラット	35	55.7	30	4.5	14	28.3	14.2	2.6	74	14.5	45	9 (M8用)	25.7
*125681	DKC12-FJ	フラット	45	67.3	35	6.1	17	35.7	20.3	3.5	96	18	60	11 (M10用)	32.3
*125682	DKC08-TJ	トウ	35	55.7	30	4.5	15.5	28.3	8.2	2.6	74	14.5	45	9 (M8用)	25.7
*125683	DKC12-TJ	トウ	45	67.3	35	6.1	18.5	35.7	9.3	3.5	96	18	60	11 (M10用)	32.3
*125684	DKC08-GJ	グリップ	35	55.7	30	4.5	20	28.3	12.7	2.6	74	14.5	45	9 (M8用)	25.7
*125685	DKC12-GJ	グリップ	45	67.3	35	6.1	28	35.7	18.8	3.5	96	18	60	11 (M10用)	32.3
*125686	DKC08-VJ	V型	35	55.7	30	4.5	17	28.3	11.2	2.6	74	14.5	45	9 (M8用)	25.7
*125687	DKC12-VJ	V型	45	67.3	35	6.1	25	35.7	12.3	3.5	96	18	60	11 (M10用)	32.3

■ 仕様・価格表

No.	N	O	P	Q	R	S	T	U	適合取付 ボルト(別売)	最大操作 トルクm	最大 締付力kN	質量 kg	価格
DKC08-FJ	19	58.3	3.8	6	19	9	M5×P0.8×8	-	M 8×16	20	10	0.8	21,000
DKC12-FJ	25	74.7	5.7	10	25	12	M6×P1.0×9	-	M10×20	50	20	1.5	26,700
DKC08-TJ	6	64.3	9.8	6	-	-	-	-	M 8×16	20	10	0.8	21,700
DKC12-TJ	8	85.7	16.7	10	-	-	-	-	M10×20	50	20	1.6	27,500
DKC08-GJ	19.5	59.8	5.3	6	-	-	-	-	M 8×16	20	10	0.8	21,700
DKC12-GJ	25	76.2	7.2	10	-	-	-	-	M10×20	50	20	1.5	27,500
DKC08-VJ	17.3	61.3	6.8	6	-	-	-	13	M 8×16	20	10	0.8	22,300
DKC12-VJ	20.6	82.7	13.7	10	-	-	-	21	M10×20	50	20	1.6	29,200